iSelf Series



Easy and flexible payment solution for self-service business

- Leverage Ingenico unattended solutions to easily integrate cashless payment in your self-service business
- Accept all payment means and comply with the latest standards
- Cut complexity in payment and security
- Address all self-service market segments: Retail, Hospitality, Petrol, Vending and Transportation













ORP-iSelf-Series-iUP250-iUC30-IUC150-EN-OC112-V1. All rights reserved. This document is not binding and the specifications above can be modified without prior consent

iSelf Series

Highest Security Levels

PCI-PTS 3.x. certified, the **iSelf** Series meets the highest and latest hardware and software security requirements. The range also complies with SRED and provides flexibility options with open protocol modules.

All Payment Options

The iUP 250 + iUR 250 enables EMV Chip and PIN, MagStripe transactions on kiosks while respecting security standards and improving customer interactivity. Transactions are simpler, faster and more secure.

Contactless Acceptance

The iUC 150 offers contactless payment, enabling e-wallet and new payment use cases. It also complies with standards such as MasterCard PayPass™, Visa PayWave™ and EMV contactless cards.

Highly Ruggedized

Thanks to its robust design the **iSelf** Series stands up to the most demanding outdoor environments and a wide variety of adverse environmental conditions. Keypad, card-reader and contactless device components are proofed against vandalism (IK10) and extreme weather.

Telium 2 Technology

Powered by Ingenico, Telium 2 Technology is the result of 30 years' experience in the payment industry. Secure, highly integrated and fast, Telium is the world's best platform to provide payment services, applications and connectivity.

Easy Integration

Our compact and modular **iSelf** Series devices are embedded in their enclosure and integrated according to EVA* / IMB** market standards. Maintenance requires no additional equipment and updating is done simply with the iUP 250 display and keypad. It is so flexible that interfacing with the entire kiosk system has never been so easy.

User-friendly

The **iSelf** Series provides a simple and easy-to-use customer interface with brightly colored backlit displays, LEDs and function keys, making their use a pleasureful experience. Transflective technology enables the **iSelf** Series to work in any lighting condition.

• Flexible Communication and Connectivity

The **iSelf** Series provides a wide range of integrated connectivity features to communicate with kiosks and acquirer hosts. It includes USB (slave, master), RS232, MDB (slave, optional master), Ethernet and optional GPRS, covering most kiosk system requirements.

Eco-friendly

Stand-by mode guarantees optimal energy efficiency. Ingenico is a reference in safeguarding the environment. Our manufacturing facilities are ISO 14001 certified.



^{**} International Metalic Bezel









		iUP 250	iUR 250	iUC 150
Processor	Туре	Risc 32-bits ARM9 Risc 32-bits ARM7	Risc 32-bits ARM7	RISC 32-bits ARM9
	Speed	450 MIPS + 50 MIPS	50 MIPS	450 MIPS
Memory	RAM/Flash	16MB/128MB	96Kb/512Kb	8MB + 16MB
Removable memory	µSD Card	1		
Communication mode	GPRS	Option		
	Ethernet	•		
	Bluetooth	Option		
SAM		2		2
SIM		Option		
Card readers	Smart card		•	
	Magstripe		ISO 1/2/3	
	Hybrid		•	
	Contactless			ISO 14443 A/B
Display	Graphic 128 x 64 pixels	•		
	Backlit RGB	•		
	Black & white	•		
Keyboard	Number of keys	15+2		
	Key texture	Metallic		
Buzzer		•	•	•
Connections	RS232	1 or 2		1
	USB Host	4		
	USB Slave	1	1	1
	MDB Slave	•		
	MDB Master	Option		
Power supply	External power supply	12V-30V DC	5V by USB Slave	5V by USB Slave
	Stand by mode	•	•	•
Size	Overall WxHxD mm	120x132x45	72x108x140	120x134x53
	Cut area W x H mm	107 x 85	74 x 62	107 x 85
Weight		620g	700g	550g
Customization				Layout sheet
Environment	Operating temperature	-20°C to +65°C	-20°C to +65°C	-20°C to +65°C
	Storage temperature	-20°C to +65°C	-20°C to +65°C	-20°C to +65°C
	Relative humidity, non condensing	90% HR at +55°C	90% HR at +55°C	90% HR at +55°C
IP	Ingress protection	IP65	IP34	IP65
IK	Shock protection	IK10	IK10	IK10
PCI PTS	3.x	•	•	



iself-service.ingenico.com ingenico.com

Discover more about our **iSelf-Service** solutions:

iSelf-Retail

iSelf-Petrol

iSelf-Hospitality

iSelf-Vending

iSelf-Transportation

